DATASHEET

Lightning and Overvoltage Protection

ProTec T1H 4+0

Class I • Class II • Type 1 • Type 2 • Type 4CA

12.5 kA Series



Location of Use: Main Distribution Boards
Network Systems: TN-S
Mode of Protection: L-PE, N-PE
IEC/EN/UL Category: Class I+II / Type 1+2 / Type 4CA
Housing: Pluggable Design
Compliance: IEC 61643-11:2011
EN 61643-11:2012+A11:2018
UL 1449 5th Edition

RoHS COMPLIANT

Technical Data


ProTec T1H-xxx-4+0(-R)		300
IEC Electrical		
Nominal AC Voltage (50/60Hz)	U_o/U_n	240 V
Maximum Continuous Operating Voltage (AC)	U_c	300 V
Nominal Discharge Current (8/20 µs)	I_n	20 kA
Maximum Discharge Current (8/20 µs)	I_{max}	65 kA
Impulse Discharge Current (10/350 µs)	I_{imp}	12.5 kA
Specific Energy	W/R	39 kJ/Ω
Charge	Q	6.25 As
Voltage Protection Level	U_p	1500 V
Response Time	t_A	< 100 ns
Overvoltage Category		III
Overcurrent Protection (max)		315 A / 250 A gG
Short-Circuit Current Rating (AC)	I_{SCCR}	25 kA / 50 kA
TOV Withstand 120min	U_T	442 V
Number of Ports		1
UL Electrical		
Maximum Continuous Operating Voltage (AC)	MCOV	300 V
Measured Limiting Voltage	MLV	1220 V
Nominal Discharge Current (8/20 µs)	I_n	20 kA
Additional Electrical Parameters - Standard *(Tests performed within Raycap testing laboratory only)*		
Residual Voltage at 5 kA (8/20 µs)	U_{res}	800 V
Minimum Backup fuse, if required		160 A gG
Additional Electrical Parameters - Extended *(Additionally tested by VDE)*		
Short-Circuit Current Rating (AC)	I_{SCCR}	100 kA
Overcurrent Protection (max)		250 A gG
Mechanical & Environmental		
Operating Temperature Range	T_a	-40 °F to +185 °F [-40 °C to +85 °C]
Permissible Operating Humidity	RH	5%...95%
Pollution Degree		2
Altitude (max)		13123 ft [4000 m]
Terminal Screw Torque	M_{max}	40 lbf·in [4.5 Nm]
Conductor Cross Section (max)		2 AWG (Solid, Stranded) / 4 AWG (Flexible)
		35 mm² (Solid, Stranded) / 25 mm² (Flexible)
Mounting		35 mm DIN Rail, EN 60715
Degree of Protection		IP 20 (built-in)
Housing Material		Thermoplastic: Extinguishing Degree UL 94 V-0
Thermal Protection		Yes
Operating State / Fault Indication		Green Flag / Not Green Flag
Remote Contacts (RC)		Optional
RC Switching Capacity		AC: 250 V / 1 A, 125 V / 1 A; DC: 48 V / 0.5 A, 24 V / 0.5 A, 12 V / 0.5 A
RC Conductor Cross Section (max)		16 AWG (Solid) / 1.5 mm² (Solid)
Overvoltage Category		III

Information contained in this document is subject to change at any time without notice.
No part of this document may be reproduced or used without written permission from Raycap.

Internal Configuration

Legend


L	*Line Conductor Terminal*
N	*Neutral Conductor Terminal*
⏚	*PE/G Conductor Terminal*
RC	*Remote Contacts Terminal (Optional)*
TD	*Thermal Disconnector*



Order Information	
Order Code	**300**
ProTec T1H-xxx-4+0	59.0316
ProTec T1H-xxx-4+0-R (with remote contacts)	59.0317
ProTec T1H-xxx-P (plug)	59.0308


Dimensions & Packaging

inches [mm]



Complete Unit		
ProTec T1H-xxx-4+0		**300**
Weight	pounds [grams]	1.389 [630]
ProTec T1H-xxx-4+0-R		
Weight	pounds [grams]	1.409 [639]
DIN 43880 Dimension		4 TE / 2.84" [72 mm]
Packaging Dimensions (H x W x L)		4.3 x 4.5 x 13.8" [109 x 115 x 352 mm]
Standard Order Quantity		4 Units

Spare Plug



Single Unit		
ProTec T1H-xxx-P		**300**
Weight	pounds [grams]	.223 [101]
DIN 43880 Dimension		1 TE / .71" [18 mm]
Packaging Dimensions (H x W x L)		4.3 x 4.5 x 13.8" [109 x 115 x 352 mm]
Standard Order Quantity		28 Units

© 2026 Raycap All rights reserved.