DATASHEET Lightning and Overvoltage Protection **12.5kA Series**

ProTec T1 3+0 LH

Class I • Class II • Type 1 • Type 2 • Type 4CA



Location of Use: Main Distribution Boards
Network Systems: TN-C
Mode of Protection: L-PEN
IEC/EN Category: Class I+II / Type 1+2 / Type 4CA
Housing: Pluggable Design
Compliance: IEC 61643-11:2011
EN 61643-11:2012+A11:2018
UL 1449 5th Edition

Technical Data


ProTec T1-xxx-3+0-LH(-R)		300
IEC Electrical		
Nominal AC Voltage (50/60Hz)	U_o/U_n	240V
Maximum Continuous Operating Voltage (AC)	U_c	300V
Nominal Discharge Current (8/20µs)	I_n	20kA
Maximum Discharge Current (8/20µs)	I_{max}	40kA
Impulse Discharge Current (10/350µs)	I_{imp}	12.5kA
Specific Energy	W/R	39kJ/Ω
Charge	Q	6.25As
Voltage Protection Level	U_p	1500V
Response Time	t_A	< 25ns
Overvoltage Category		III
Maximum Backup fuse, if required		160A gG
Short-Circuit Current Rating (AC)	I_{SCCR}	50kA
TOV Withstand 5s	U_T	337V
TOV 120min	U_T	442V
	mode	Safe Fail
Number of Ports		1
UL Electrical		
Maximum Continuous Operating Voltage (AC)	MCOV	300V
Measured Limiting Voltage	MLV	1200V
Nominal Discharge Current (8/20µs)	I_n	20kA
Additional Electrical Parameters *(Tests performed within Raycap testing laboratory only)*		
Residual Voltage at 5 kA (8/20 µs)	U_{res}	700V
Minimum Backup fuse, if required		160A gG
Mechanical & Environmental		
Operating Temperature Range	T_a	-40 °F to +185 °F [-40 °C to +85 °C]
Permissible Operating Humidity	RH	5%...95%
Pollution Degree		2
Altitude (max)		13123 ft [4000m]
Terminal Screw Torque	M_{max}	40 lbf·in [4.5Nm]
Conductor Cross Section (max)		2 AWG (Solid, Stranded) / 4 AWG (Flexible)
		35mm² (Solid, Stranded) / 25mm² (Flexible)
Mounting		35mm DIN Rail, EN 60715
Degree of Protection		IP 20 (built-in)
Housing Material		Thermoplastic: Extinguishing Degree UL 94 V-0
Thermal Protection		Yes
Operating State / Fault Indication		Green Flag / Not Green Flag
Remote Contacts (RC)		Optional
RC Switching Capacity		AC: 250V/1A, 125V/1A; DC: 48V/0.5A, 24V/0.5A, 12V/0.5A
RC Conductor Cross Section (max)		16 AWG (Solid) / 1.5mm² (Solid)
Overvoltage Category		III

Information contained in this document is subject to change at any time without notice.
No part of this document may be reproduced or used without written permission from Raycap.

Internal Configuration

Legend


L	*Line Conductor Terminal*
⏚	*PEN/G Conductor Terminal*
RC	*Remote Contacts Terminal (Optional)*
TD	*Thermal Disconnector*



Order Information	
Order Code	**300**
ProTec T1-xxx-3+0-LH	59.A375
ProTec T1-xxx-3+0-LH-R (with remote contacts)	59.A376
ProTec T1-xxx-LH-P (plug)	59.A383


Dimensions & Packaging

inches [mm]



Complete Unit		
ProTec T1-xxx-3+0-LH		**300**
Weight	pounds [grams]	1.177 [534]
ProTec T1-xxx-3+0-LH-R		
Weight	pounds [grams]	1.190 [540]
DIN 43880 Dimension		3 TE / 2.13" [54 mm]
Packaging Dimensions (H x W x L)		4.3 x 4.5 x 13.8" [109 x 115 x 352 mm]
Standard Order Quantity		5 Unit

Spare Plug



Single Unit		
ProTec T1-xxx-LH-P		**300**
Weight	pounds [grams]	.255 [116]
DIN 43880 Dimension		1 TE / .71" [18 mm]
Packaging Dimensions (H x W x L)		4.3 x 4.5 x 13.8" [109 x 116 x 352 mm]
Standard Order Quantity		24 Units

© 2026 Raycap All rights reserved.