DATASHEET

Pluggable Multi-Pole SPD for DC Systems

ProTec T2 DCU 3Y

Class II • Type 2 • DC SPD Type 1

Unipolar



Location of Use: DC Systems, EV Chargers
Network Systems: Unipolar grounded / ungrounded, TN, TT*, IT*
Mode of Protection: (+)-PE/G, (-)-PE/G, (+)-(-)
IEC/EN/UL Category: Class II/Type 2/DC SPD Type 1
Housing: Pluggable Design
Compliance: IEC 61643-41:2025
EN IEC 61643-41:2025
UL 1449 5th Edition, Supplement SB

Technical Data


ProTec T2-xxxxDCU-3Y(-R)			500	1000	1500
IEC Electrical					
Nominal DC System Voltage	(+)-(-)	U_n	500 V	1000 V	1500 V
Maximum Continuous Operating Voltage (DC)		U_c	500 V	1000 V	1500 V
Nominal Discharge Current (8/20 µs)		I_n	20 kA	20 kA	20 kA
Maximum Discharge Current		I_{max}	40 kA	40 kA	40 kA
Total Discharge Current (8/20 µs)		I_{Total}	70 kA	70 kA	55 kA
Voltage Protection Level		U_p	2400 V	3150 V	3700 V
Response Time		t_A		< 25 ns	
Overvoltage Category				III	
Overcurrent Protection (max)			200 A gBat**	200 A gBat***	200 A gBat***
Short-Circuit Current Rating (DC)		I_{SCCR}		30 kA (L/R < 3 ms)	
Number of Ports				1	
UL Electrical					
Maximum Permitted DC Voltage		V_{dcmcov}	500 V	1000 V	1500 V
Voltage Protection Rating		VPR	1800 V	2500 V	3000 V
Nominal Discharge Current (8/20 µs)		I_n		20 kA	
Short-Circuit Current Rating (DC)		SCCR		100 kA	
Additional Electrical Parameters *(Tests performed within Raycap testing laboratory only)*					
Residual Voltage at 5 kA (8/20 µs)		U_{res}	1800 V	2500 V	3000 V
Impulse Discharge Current (10/350 µs)		I_{imp}	5 kA	5 kA	2.8 kA
Total Discharge Current (10/350 µs)		I_{Total}	10 kA	10 kA	3 kA
Mechanical & Environmental					
Operating Temperature Range		T_a	-40 °F to +185 °F [-40 °C to +85 °C]		
Permissible Operating Humidity		RH	5%...95%		
Pollution Degree			2		
Altitude (max)			6562 ft [2000 m]		
Terminal Screw Torque		M_{max}	35 lbf·in per UL 1449 [4.5 Nm]		
Conductor Cross Section (max)			6 AWG (Solid, Stranded) per UL 1449		
			35 mm² (Solid, Stranded) / 25 mm² (Flexible)		
			Cu Only per UL 1449		
Mounting			35 mm DIN Rail, EN 60715		
Degree of Protection			IP 20 (built-in)		
Housing Material			Thermoplastic: Extinguishing Degree UL 94 V-0		
Thermal Protection			Yes		
Operating State / Fault Indication			Green Flag / Not Green Flag		
Remote Contacts (RC)			Optional		
RC Switching Capacity			AC: 125 V / 1 A; DC: 48 V / 0.5 A, 24 V / 0.5 A, 12 V / 0.5 A		
RC Conductor Cross Section (max)			16 AWG (Solid) / 1.5 mm² (Solid)		
Overvoltage Category			III		

*Only for DC power systems which are electrically separated from AC power systems.
**ETI NH1 BAT 200A/550V DC (004723266), ***ETI NH1 BAT 200A/1500V DC (004110656)


Raycap

Information contained in this document is subject to change at any time without notice.
No part of this document may be reproduced or used without written permission from Raycap.

Internal Configuration



ProTec T2-500DCU-3Y(-R)
ProTec T2-1000DCU-3Y(-R)



ProTec T2-1500DCU-3Y(-R)

Legend


⏚	*PE / G Conductor Terminal*
RC	*Remote Contacts Terminal (Optional)*
TD	*Thermal Disconnector*

Order Information

Order Code	500	1000	1500
ProTec T2-xxxxDCU-3Y	59.A983	59.A985	59.A987
ProTec T2-xxxxDCU-3Y-R (with remote contacts)	59.A984	59.A986	59.A988
ProTec T2-250DCU-M-P (side plug)	59.A989	-	-
ProTec T2-250DCU-P (middle plug)	59.A990	-	-
ProTec T2-500DCU-M-P (side plug)	-	59.A991	-
ProTec T2-500DCU-P (middle plug)	-	59.A992	-
ProTec T2-750DCU-M-P (plug)	-	-	59.A993

Dimensions & Packaging


inches [mm]




Complete Unit

ProTec T2-xxxxDCU-3Y		**500**	**1000**	**1500**
Weight	pounds [grams]	.772 [350]	.831 [377]	.791 [359]
ProTec T2-xxxxDCU-3Y-R				
Weight	pounds [grams]	.789 [358]	.849 [385]	.809 [367]
DIN 43880 Dimension		3 TE / 2.13" [54 mm]		
Packaging Dimensions (H x W x L)		4.3 x 4.5 x 13.8" [109 x 115 x 352 mm]		
Standard Order Quantity		5 Units		

Spare Plug



ProTec T2-250DCU-M-P
ProTec T2-500DCU-M-P
ProTec T2-750DCU-M-P



ProTec T2-250DCU-P
ProTec T2-500DCU-P

Single Unit

ProTec T2-xxxDCU-M-P		**250**	**500**	**750**
Weight	pounds [grams]	.141 [64]	.161 [73]	.146 [66]
ProTec T2-xxxDCU-P				
Weight	pounds [grams]	.134 [61]	.157 [71]	-
DIN 43880 Dimension		1 TE / .70" [18 mm]		
Packaging Dimensions (H x W x L)		3.2 x 4.5 x 12" [83 x 116 x 305 mm]		
Standard Order Quantity		24 Units		

© 2026 Raycap All rights reserved.