




IEC/EN Category: C1/C3
 Surge Discharge Ratings: I_n : 250 A
 Voltages: 30 V DC
 Frequency Range: 30 MHz
 Housing: Modular Design
 Compliance: IEC/EN 61643-21
 UL 497B 4th Edition

Configuration:

**Technical Data****SLL-4 Series****30****Electrical**

Lines Protected		2 (4 Conductors)
Nominal Operating Voltage (DC)	U_n	30 V
Maximum Continuous Operating Voltage (DC)	U_c	33 V
Rated Load Current at 25°C	I_L	10 A
C1 Nominal Discharge Current (8/20 μs)	I_n	250 A
Residual Voltage at 5 kA (8/20 μs)	(Line-Line) U_{res}	< 80 V
Rated Spark Overvoltage	(Line-Line)	36-44 V
	(Line-Ground)	36-44 V
Response Time Overvoltage Protection	(Line-Line) t_A	< 1 ns
	(Line-Ground)	< 1 ns
Insulation Resistance of the Protection	(Line-Line) R_{iso}	≥ 33 MΩ
	(Line-Ground)	≥ 33 MΩ
Serial Resistance per Path	R	0.1 Ω
Transverse Capacitance	(Line-Line) C	50 pF
	(Line-Line)	50 pF
Cut-off Frequency	f_G	30 MHz

Mechanical

Temperature Range	-40 °F to +176 °F [-40 °C to +80 °C]
Terminal Cross Section Multi-strand (max.)	12 AWG [4 mm², 2.5 mm² Q Version]
Terminal Screw Torque	4.5 lbf-in [0.5 Nm]
Degree of Protection IEC/EN 60529	IP 20 (built-in)
Housing Material	Thermoplastic; Grey; Extinguishing Degree V-0
Mounting IEC/EN 60715	35 mm DIN Rail

Order Information


Order Code	30
SLL-4-xx	7082.92
SLL-4-xxQ (Quick Connect Terminals)	7085.27
SLL-4-xxM (module)	7082.93

RayDat SLL-4 Series



Internal Configuration

Legend

DB Diode Block
PG Protective Grounding



Dimensions & Packaging



SLL-4 Series

30

Dimensions

Weight per Unit	1.97 oz [56 g]
Dimensions DIN 43880	2/3 TE
Packaging Dimensions (Single Unit)	3.4 x .59 x 4" [87 x 15 x 102 mm]
Minimum Package Quantity	15 pieces


SLL-4-xxM Series

30

Dimensions

Weight per Unit	.77 oz [22 g]
Packaging Dimensions (Single Unit)	3.4 x .59 x 4" [87 x 15 x 102 mm]
Minimum Package Quantity	15 pieces

Quick Connect Terminals



SLL-4-xxQ Series

30

Dimensions

Weight per Unit	2.04 oz [58 g]
Dimensions DIN 43880	2/3 TE
Packaging Dimensions (Single Unit)	3.4 x .59 x 4" [87 x 15 x 102 mm]
Minimum Package Quantity	15 pieces

inches
[mm]

Information contained in this document is subject to change at any time without notice.



Raycap

www.raycap.com

© 2020 Raycap All rights reserved.
G29-00-697 201120